Tempo2 Universal Two Stage Timer

Rev. DSTempo2 - E04F

Overview

- This unit is suitable for applications that require timed operations. A delayed egress feature will trigger a 1 to 60 second door release. Applications include daily/weekly test mode, one shot, door prop alarm, timed door annunciate, cut-off timer, alarm swinger eliminator, etc. Digital display facilitates ease of programming and real time information.

Specifications

- 12 or 24 Volts AC or DC operation.
- Triggers via positive DC (+) voltage, dry contact closure, or removal of contact closure.
- Dry Form "C" contacts are rated @ 2 amp/120VAC/28VDC.
- LCD displays real time countdown information.
- Current draw: stand-by 15mA, relay energized 30mA.
- EE Prom memory protects against loss of programming due to power failure.
- Simple programming.

One-Shot Features (trigger activated):

- Programmable relay activation at the start or end of the timing cycle.
  a. Delayed Pulse Mode:
  1 to 60 sec. programmable pulse at the end of timing cycle.
  b. Delay Mode:
  Relay can be programmed to energize or de-energize during timing cycle (Digitally adjust from 1 sec.-24hours).
- Product weight: .10 lbs.
- Shipping weight: .20 lbs.

Board Dimensions (approximate)

2.5"W x 3"L x 0.75"D

Mounting Diagram